


# SERTSEM CF-200 FR TECHNICAL SPECIFICATIONS

|                              |   |
|------------------------------|---|
| <b>Casing Material:</b>      | Polycarbonate   |
| <b>Dimensions:</b>           | 280 x 54 x 62 mm.   |
| <b>Type of protection:</b>   | Fuse holder for cylindrical 10x38 T-0 cartridge fuse  |
| <b>Degree of protection:</b> | IP44 with medium AC according to EN 60529<br>IK08 UNE-EN 50102:1996+A1:1999+corr:2002+A1CORR:2002 |
| <b>CE Marking</b>            |   |

|                       |   |
|-----------------------|---|
| <b>Insulation:</b>    |  Double insulation<br>Class II |
| <b>Installation:</b>  | The connection is made outside the staff/column; it can also be fitted to facades and posts.                    |
| <b>Safety:</b>        | Dielectric Strength UNE 21095-73  |
| <b>Certification:</b> | Certified under ENAC homologated standards.   |
| <b>Quality:</b>       | ISO 9001:2008 STANDARD  |

| Models         | Nr. Poles       | Max. Admittance<br>Terminals Input/<br>Output | Derivation<br>Terminals | Auxiliary<br>terminals | Packaging<br>(units) |
|----------------|-----------------|---|-------------------------|------------------------|----------------------|
| CF-200 FR      | 3P + N          | 25 mm <sup>2</sup>                            | 0                       | 0                      | 25                   |
| CF-200 FR-BAUX | 3P + N + 3 PAUX | 25 mm <sup>2</sup>                            | 0                       | 2 X 16 mm <sup>2</sup> | 25                   |

## ACCESSORIES FOR THE DIFFERENT LIGHTING SETUPS

MINI accessory: Up to two 16mm<sup>2</sup> cables.

MEDIUM accessory: Up to two 20mm<sup>2</sup> cables.

MAXI accessory: Up to two 25mm<sup>2</sup> cables.

