

<b>Casing Material:</b>	Polycarbonate
<b>Dimensions:</b>	280 x 54 x 62 mm.
<b>Type of protection:</b>	Fuse holder for cylindrical 10x38 T-0 cartridge fuse
<b>Degree of protection:</b>	IP44 with medium AC according to EN 60529 IK08 UNE-EN 50102:1996+A1:1999+corr:2002+A1CORR:2002
<b>CE Marking</b>	

<b>Insulation:</b>	<input type="checkbox"/> Double insulation Class II
<b>Installation:</b>	The connection is made outside the staff/column; it can also be fitted to facades and posts.
<b>Safety:</b>	Dielectric Strength UNE 21095-73
<b>Certification:</b>	Certified under ENAC homologated standards.
<b>Quality:</b>	ISO 9001:2008 STANDARD

Models	Nr. Poles	Max. Admittance Terminals Input/ Output	Derivation Terminals	Auxiliary terminals	Packaging (units)
CF-200	3P + N	2 X 16 mm <sup>2</sup>	2 X 6 mm <sup>2</sup>	0	25
CF-200-BAUX	3P + N + 3 PAUX	2 X 16 mm <sup>2</sup>	2 X 6 mm <sup>2</sup>	2 X 16 mm <sup>2</sup>	25

### ACCESSORIES FOR THE DIFFERENT LIGHTING SETUPS

MINI accessory: Up to two 16mm<sup>2</sup> cables.

MEDIUM accessory: Up to two 20mm<sup>2</sup> cables.

MAXI accessory: Up to two 25mm<sup>2</sup> cables.

