

SERTSEM CF-200 MAG TECHNICAL SPECIFICATIONS

Casing Material:	Polycarbonate
Dimensions:	280 x 54 x 62 mm.
Type of protection:	Fuse holder for cylindrical 10x38 T-0 cartridge fuse
Degree of protection:	IP44 with medium AC according to EN 60529
CE Marking	IK08 UNE-EN 50102:1996+A1:1999+corr:2002+A1CORR:2002

Insulation:	<input type="checkbox"/> Double insulation Class II
Installation:	The connection is made outside the staff/column; it can also be fitted to facades and posts.
Safety:	Dielectric Strength UNE 21095-73
Certification:	Certified under ENAC homologated standards.
Quality:	ISO 9001:2008 STANDARD

Models	Nr. Poles	Max. Admittance Terminals Input/ Output	Derivation Terminals	Auxiliary terminals	Packaging (units)
CF-200 MAG	3P + N	2 X 16 mm ²	2 X 6 mm ²	0	20
CF-200 MAG-BAUX	3P + N + 3 PAUX	2 X 16 mm ²	2 X 6 mm ²	2 X 16 mm ²	20

ACCESSORIES FOR THE DIFFERENT LIGHTING SETUPS

MINI accessory: Up to two 16mm² cables.

MEDIUM accessory: Up to two 20mm² cables.

MAXI accessory: Up to two 25mm² cables.

