






SERTSEM CF-106/M TECHNICAL SPECIFICATIONS

Casing Material:	Polycarbonate
Dimensions:	165 x 135 x 73 mm.
Type of Protection:	Fuse holder for cylindrical 10x38 T-0 cartridge fuses
Degree of protection:	IP 44 with AC001 - IP 13 with AC002 according to norm EN 60529
CE Marking	IK08 UNE-EN 50102:1996+A1:1999+corr:2002+A1CORR:2002

Insulation:	 Measurement of creepage lines and air distance UNE 20098-75 Double insulation
Installation:	The connection is made outside the staff/column, it can also be fitted to facades and posts. Connection/disconnection of fuses by a frontal pressure/ extraction cover.
Safety:	Dielectric Strength UNE 21095-73
Certification:	Certified under ENACs homologated standards.
Quality:	ISO 9001:2008 STANDARD

Models	Nr. Poles	Max. Admittance Terminals Input/ Output	Derivation Terminals	Auxiliary terminals	Packaging (units)
(2) CF-106/M	3P + N	2 X 35 mm ²	2 X 6 mm ²	0	25
(1) CF-106/M4	3P + N	2 X 35 mm ²	2 X 6 mm ²	0	25
(2) CF-106-T/M	3P + N+ 	2 X 35 mm ²	2 X 6 mm ²	2 X 16 mm ²	25
(2) CF-106/M-C	3P + N+2 PAUX	2 X 35 mm ²	2 X 6 mm ²	2 X 16 mm ²	25
(1) CF-106/M4-C	3P + N+2 PAUX	2 X 35 mm ²	2 X 6 mm ²	2 X 16 mm ²	25
(1) CF-106-T/M4	3P + N+ 	2 X 35 mm ²	2 X 6 mm ²	2 X 16 mm ²	25
(2) CF-106/M/12	3P + N	2 X 25 mm ²	2 X 6 mm ²	0	25
(1) CF-106/M4/12	3P + N	2 X 25 mm ²	2 X 6 mm ²	0	25
(2) CF-106-T/M/12	3P + N+ 	2 X 25 mm ²	2 X 6 mm ²	2 X 16 mm ²	25
(2) CF-106/M-C/12	3P + N+2 PAUX	2 X 25 mm ²	2 X 6 mm ²	2 X 16 mm ²	25
(1) CF-106/M4-C/12	3P + N+2 PAUX	2 X 25 mm ²	2 X 6 mm ²	2 X 16 mm ²	25
(1) CF-106-T/M4/12	3P + N+ 	2 X 25 mm ²	2 X 6 mm ²	2 X 16 mm ²	25

Notes: (1) 4 Fuses Box, (2) 2 Fuses Box.
The four fuse boxes are equipped with connections to protect the light fitting through different phases.

