





<b>Casing Material:</b>	Polycarbonate
<b>Dimensions:</b>	165 x 105 x 68 mm.
<b>Type of Protection:</b>	Fuse holder for cylindrical 10x38 T-0 cartridge fuses
<b>Degree of protection:</b>	IP 44 with AC001 - IP 13 with AC002 according to norm EN 60529
<b>CE Marking</b>	IK08 UNE-EN 50102:1996+A1:1999+corr:2002+A1CORR:2002

<b>Insulation:</b>	 Measurement of creepage lines and air distance UNE 20098-75 Double insulation
<b>Installation:</b>	The connection is made outside the staff/column, it can also be fitted to facades and posts. Connection/disconnection of fuses by a frontal pressure/ extraction cover.
<b>Safety:</b>	Dielectric Strength UNE 21095-73
<b>Certification:</b>	Certified under ENACs homologated standards.
<b>Quality:</b>	ISO 9001:2008 STANDARD

Models	Nr. Poles	Max. Admittance Terminals Input/ Output	Derivation Terminals	Auxiliary terminals	Packaging (units)
(1) CF-105	3P + N	2 X 35 mm <sup>2</sup>	2 X 6 mm <sup>2</sup>	0	30
(1) CF-105-T	3P + N + 	2 X 35 mm <sup>2</sup>	2 X 6 mm <sup>2</sup>	2 X 16 mm <sup>2</sup>	30
(1) CF-105-C	3P +N+2 PAUX	2 X 35 mm <sup>2</sup>	2 X 6 mm <sup>2</sup>	2 X 16 mm <sup>2</sup>	30
(2) CF-105-2	3P + N	2 X 35 mm <sup>2</sup>	2X 6 mm <sup>2</sup>	0	30
(2) CF-105-2T	3P + N + 	2 X 35 mm <sup>2</sup>	2 X 6 mm <sup>2</sup>	2 X 16 mm <sup>2</sup>	30
(2) CF-105-2C	3P +N+2 PAUX	2 X 35 mm <sup>2</sup>	2 X 6 mm <sup>2</sup>	2 X 16 mm <sup>2</sup>	30

Notes: (1) 4 Fuses Box, (2) 2 Fuses Box.  
The four fuse boxes are equipped with connections to protect the light fitting through different phases.



AC 002 Rubber Fringe entry.