






Casing Material:	Polycarbonate
Dimensions:	180 x 83 x 51 mm.
Type of Protection:	Fuse holder for cylindrical 10x38 T-0 cartridge fuses
Degree of protection:	IP 54 with AC001 according to EN 60529
CE Marking	IK10 UNE-EN 50102:1996+A1:1999+corr:2002+A1CORR:2002

Insulation:	 Measurement of creepage lines and air distance UNE 20098-75 Double insulation
Installation:	Designed to be fitted only on facades and posts. Connection/disconnection of fuses by a vertical movement casing.
Safety:	Dielectric Strength UNE 21095-73
Certification:	Certified under ENACs homologated standards.
Quality:	ISO 9001:2008 STANDARD

Models	Nr. Poles	Max. Admittance Terminals Input/ Output	Derivation Terminals	Auxiliary terminals	Packaging (units)
CM	3P + N	2 X 16 mm ²	2 X 6 mm ²	0	50
CM-T	3P + N+ 	2 X 16 mm ²	2 X 6 mm ²	2 X 16 mm ²	50
CM-C	3P + N+2 PAUX	2 X 16 mm ²	2 X 6 mm ²	2 X 16 mm ²	50
CM-CT	3P + N+  2PAUX	2 X 16 mm ²	2 X 6 mm ²	2 X 16 mm ²	50
CM/35	3P + N	2 X 35 mm ²	2 X 6 mm ²	0	50
CM-T/35	3P + N+ 	2 X 35 mm ²	2 X 6 mm ²	2 X 16 mm ²	50
CM-C/35	3P + N+2 PAUX	2 X 35 mm ²	2 X 6 mm ²	2 X 16 mm ²	50
CM-CT/35	3P + N+  2 PAUX	2 X 35 mm ²	2 X 6 mm ²	2 X 16 mm ²	50



AC 001 Rubber Gland.